

LUBKLEAR™ 90 NF WHITE MINERAL OIL

PROPERTIES	METHOD	SPECIFICATIONS		
		Result	Min.	Max.
Appearance	A-8039	Bright	Bright	Bright
Color, Saybolt	D-156	+30	30	
Flash Point COC °F (°C)	D-92	391 (199)		
Gravity, °API	D-4052	34.8	30.0	35.0
Gravity, Specific 25/25 °C	D-4052	0.8540	0.833	0.872
Viscosity, cSt @ 40 °C	D-445	15.75	14.2	17.0
Viscosity, SUS @ 100 °F	D-445	87.5	78	94
UV Absorbance, 21 CFR 172.878	FDA	Pass		
Limit of Sulfur Compounds	USP	Pass		
Limit of Polycyclic Aromatic Hydrocarbons	USP	Pass		
Readily Carbonizable Substances	USP	Pass		
Solid Paraffin	USP/NF	Pass		
Acidity	USP	Pass		

LUB- \diamond -LINE Mineral White Oil meets the requirements of FDA and U.S. Regulations 21 CFR 172.878 and 178.3620 for direct and indirect food contact.

LUB- \diamond -LINE Mineral White Oil is a food grade white mineral oil meeting all requirements, as currently defined by the United States Pharmacopeias for USP Mineral Oils.

LUB- \diamond -LINE Mineral White Oil is NSF registered as an H1 and 3H lubricant for use in and around food processing areas under the jurisdiction of the USDA.