

LUBKLEAR™ 350 USP

WHITE MINERAL OIL

Property	Test Method	Specification	Typical Values
Density @ 15°C	ASTM D4052	Report	0.869
Specific gravity @ 25°C/25°C	ASTM D4052	0.855 - 0.880	0.865
Viscosity @40°C, cSt	ASTM D0445	66 - 71	68
Viscosity @100°F, SUS	ASTM D2161	Report	350
Odor	PCM532	Neutral-Pass	Pass
Appearance	Visual	Clear & Bright	Clear & Bright
Colour, Saybolt	ASTM D0156	+30 min	+30
Pour Point, °C (°F)	ASTM D0097	Report	-12 (10)
Flash Point, COC, °C (°F)	ASTM D0092	Report	230 (446)
Readily Carbonizable Substances	USP (current revision)	Pass	Pass
Neutrality	USP (current revision)	Pass	Pass
Solid Paraffins	USP (current revision)	Pass	Pass
Limit of Polynuclear Compounds	USP (current revision)	Pass	Pass
Sulfur Compounds	USP XVII	Pass	Pass

LUB<gtLINE Mineral White Oil meets the requirements of U.S. Regulations 21 CFR 172.878 and 178.3620 for direct and indirect food contact. LUB<gtLINE Mineral White Oil is a food grade white mineral oil meeting all requirements, as currently defined by the United States Pharmacopeias for USP Mineral Oils.

LUB<gtLINE Mineral White Oil is NSF registered as an H1 and 3H lubricant for use in and around food processing areas under the jurisdiction of the USDA.