

HARVESTOL[™] 2

Agricultural Oil

PROPERTY	SPECIFICATION	TYPICAL VALUE	METHOD
Total n-Paraffin Wt%	96.5 min	98	GC
C13	1 max	0.5	GC
C14	50-65	58	GC
C15+	Balance	39.5	GC
Average Molecular Weight	-	205	GC
Aromatics, wt%	0.5 max	0.01	UV Analysis
Bromine Number	-	<0.04	Modified ASTM D-1159
Color Saybolt	30+min	30	ASTM D-156
Specific Gravity @ 60°F	-	0.773	ASTM D-287
Total Acid Number		0.1mg/KOH/g	ASTM D-974
Unsulphonated mineral residue		<92%	ASTM D-483
Density @ 60°F, lb/gal	-	6.45	ASTM D-287
Flash Point (PMCC) °F/°C	-	245/118	ASTM D-93
Melt Point, °F/°C	-	50/10	ASTM D-2386
Viscosity. cSt @ 40°C/104 °F	-	2.5	ASTM D-445
Distillation Range, °F/°C			ASTM D-86
IBP	-	489/254	
EP	-	541/283	
Appearance	-	Clear Liquid	Visual
Kauri Butanol Value	-	20	ASTM D-1133
Sulfur, ppm	-	<1	Pyro/flour
Aniline Point, °F/°C	-	198/92	ASTM D-611

LUBLINE Harvestol[™] 2 exhibits low toxicity and it is biodegradable. No adverse health effects would be expected when properly handled and used. Consequently, no special precautions are necessary in handling the banana spray oil. Please consult the manufacturer's recommendations concerning handling the fungicides and the pesticides.