

## LUBPAR<sup>™</sup> 1000

Solvent is a synthetic high-performance, low-environmental impact alternative to diesel fuel and certain mineral oils. LubPar 1000<sup>™</sup> Solvent is a value-added alternative in high performance industrial applications because of its low toxicity, improved biodegradability over diesel, and the absence of polynuclear aromatics.

PROPERTY	TYPICAL VALUE
<i>Aniline Point, °C (°F)</i>	66 (151)
<i>Kauri Butanol Value</i>	18
<i>Boiling Point, °C (°F)</i>	211 (412)
<i>IBP</i>	224 (436)
<i>5%</i>	363 (685)
<i>95%</i>	364 (687)
<i>EBP</i>	
<i>Color, APHA</i>	< 100
<i>Density, lbs/gal @ 16°C</i>	6.74
<i>Specific Gravity, @ 20°C (68°F)</i>	0.8045
<i>Flash Point, °C (°F)</i>	80 to >93 (175 to >200)
<i>API Gravity, @ 16°C (60 °F)</i>	43.7
<i>Melting Range, °C (°F)</i>	-6 to 9 (21 to 48)
<i>Pour Point, °C (°F)</i>	0 (32)
<i>Vapor Pressure, mm Hg @ 20°C</i>	0.41
<i>Viscosity, cSt</i>	3.3
<i>40°C</i>	1.4
<i>100°C</i>	
<i>Autoignition temp., °C (°F)</i>	248 (478)
<i>VOC (EPA Method 24), %</i>	74
<i>BTEX, mg/kg</i>	N.D.
<i>PAH, mg/kg</i>	<0.3